



MATERIAL OF CONSTRUCTION:

Sr.	DESCRIPTION	MATERIAL SPEC.
1)	FOAM CHAMBER	M.S. TO IS:226
2)	PIPE	M.S.M.D. TO IS:1239
3)	ORIFICE PLATE	BRASS TO IS:410
4)	FLANGES	M.S. PLATE TO IS:226
5)	VAPOURSEAL	GLASS
6)	AIR STRAINER	AL. ALLOY TO IS:617

WORKING PRESSURE : 3 TO 7 Kg/cm²

HYDRAULIC TEST PRESSURE : 15 Kg/cm²

VAPOURSEAL BURST PRESSURE : 1 TO 1.5 Kg/cm²

FINISH : GALVANISED & PAINTED ANTICORROSIVE FIRE RED / YELLOW.

PERFORMANCE DATA:

MODEL	WATER FLOW IN LPM @ 7Kg/cm ²	A mm	B mm	C mm	D mm	N1 NB	N2 NB	WEIGHT IN KG
A	75 TO 225	500	260	135	120	50	80	14.000
B	225 TO 450	665	390	200	180	65	100	26.500
C	450 TO 900	820	500	255	230	80	125	39.500
D	900 TO 1800	910	530	310	255	100	150	65.500
E	1800 TO 2700	1090	650	405	305	150	200	108.000

EVERSAFE
PROTECTION

FOAM MAKER WITH
VAPOURSEAL CHAMBER

DATA SHEET.NO.

640